Belinea

[Belinea 10 17 15]

Low priced entry to the 17-inch-area

In the latest generation of the Belinea 10 17 15 the price keeps being attractive.

With high contrast and brightness values this display shows that good quality need not be expensive. Due to the short response time of 20 ms and the integrated speakers the Belinea 10 17 15 also allows multimedia applications. Certifications like TCO99 and ISO 13406-2 demonstrate the high quality of this entry display.

D-Sub connection for analogue graphics cards



Integrated speaker



Belinea 10 17 15 – The entry to the 17-inch-area

- 17 inch (43.18 cm)
- analogue
- Sound, TN-Panel
- Viewing angle: 150° / 130°
- Response time rise / fall: 4 / 16 ms

Target Groups

- **Small and Medium Business**
- **Price sensitive users**
- **Video applications**

MAXDATA Computer GmbH & Co. KG • Elbestraße 12-16 • D-45768 Marl • www.maxdata.de

11/2003 ® Erros and omissions exempt.

MAXDATA
REAL HARD WARE

Belinea 10 17 15 – Technical Data

Panel characteristics

Image size	17“
Viewable image size in inch / cm	17“ / 43.18
Max. picture size (w x h) in mm	337.9 x 270.3
Physical resolution	1280 x 1024
Pixel pitch in mm	0.264 x 0.264
Active Matrix, TFT	•
Displayable colours (max.)	16.2 Mio (FRC)
Brightness in cd / qm	300
Contrast ratio	450:1
Viewing angle horizontal	150°
Viewing angle vertikal	130°
Coating	Anti Glare
Responsetime: rise / fall in ms	4 / 16
Panel technology	TN
Back Light	4 CCFLs

Electronic data

Horizontal frequency in kHz	31 - 81
Vertical frequency in Hz	56 - 75
Bandwidth in MHz	135
Input voltage 110-230V, 50-60 Hz	•
Power consumption in Watt (On / Sleep)	50 / 1
Input signal (VGA-card) analog / digital	• / –
Output audio amplifier	2 x 1 Watt

Features

Factory / user defined modes	16 / 9
OSD	•
Integrated microphone	–
Integrated speaker	•
Power supply in the panel / in the stand / external	• / – / –
Tilt back / forth	25° / 5°
Swivel right / left	– / –

Controls

Brightness / contrast	• / •
H / V position	• / •
Automatic picture-adjustment / colour calibration	external / •
Temperatur	•
Fine adjustment horizontal (clock) / vertical (phase)	• / •
Display at lower resolutions: 1:1 / full screen	– / •
Zoom / frequency	– / •
Recall / video signal selection	• / –
OSD position / OSD language(s)	• / 5
Mute	external
Volume	external

Max. refresh rates in Hz with resolution

640 x 480	75
800 x 600	75
1024 x 768	75
1152 x 864	75
1280 x 1024	75

Approvals / Standards

Plug & Play, DDC1 / 2B	•
Power-Management:	
Energy Star / Energy Label	• / •
TCO99	•
TÜV GS / TÜV Ergonomie	• / •
DIN 29241 / ISO 9241-3, -7, -8 / ISO 13406-2	• / • / •
Compliant to mountings acc.to VESA standard	•
MAC compliant	•

Connections

15-pin Mini-D-Sub	•
24-pin DVI-D	–
Headphone plug	–
Audio In	•

Accessories

User manual (languages)	10
Power cable	•
Video connect. 15-pin Mini-D-Sub	• (non detachable)
Video connect. 24-pin DVI-D	–
Audio cable	•
Optional accessories	–
Microphone cable	–

Physical specification

Size (w x h x d) in mm	375 x 393 x 182
Net / gross weight in kg	4.6 / 6.8

Austria
MAXDATA Computer GmbH
Ignaz-Köck-Straße 9 • 1210 Wien

Benelux
MAXDATA Benelux B.V.
Bredaseweg 113-115 • 4872 LA Etten-Leur

España • Portugal
MAXDATA Iberia
c/ Collado mediano, s/n • Edificio Prisma
Portal 1-Pta. 1ª B • E-28230-Las ROZAS, Madrid

France
MAXDATA S.A.R.L.
1, rue de Gevaudan • SILIC 1726
91017 EVRY Cedex

Germany
MAXDATA Computer GmbH & Co. KG
Elbestraße 12-16 • 45786 Marl

Italy
MAXDATA Italia S.r.l.
Strada 1 • Palazzo F1
I-20090 Milanofiori, Assago (MI)

Poland
MAXDATA Sp. z o.o.
Ursynów Business Park • Ul. Pulawska 303
02-785 Warszawa

Switzerland
MAXDATA Computer AG
Haldenstrasse 5 • 6340 Baar

United Kingdom
MAXDATA UK Limited
The MAXDATA Centre • Downmill Road
Bracknell, Berkshire RG12 1QS

With compliments: